

# HOT WATER BOILERS

*Our boilers meet the requirements of all hot cure applications, small diameter to large.*

Our 1,000,000 BTU and 2,000,000 BTU boilers are skid mounted and can be moved between vehicles or installed into trailers.

*We design boilers to the unique specification of our customers.*

*Please contact us for further information and capabilities.*

SIZE	200,000 BTU to 4,000,000 BTU
OPTIONS	Portable units, skid mounted or vehicle installed.



# HOT WATER BOILERS

**HOT WATER BOILER SPECIFICATION TABLE**

Boiler Specifications	200,000 BTU	500,000 BTU	1,000,000 BTU	2,000,000 BTU
Duty (kW/BTU)		145/500,000	290/1,000,000	580/2,000,000
Fuel Type	Diesel	Diesel	Diesel	Diesel
Burner Control	Single Stage	Single Stage	2 Stage Hi/Low	2 Stage Hi/Low
Generator Requirement	2.5Kva Single Phase 240V	3.5Kva Single Phase 240V	4.5Kva/Single Phase 240V	8.5Kva/3 Phase 415V
Temp Range	0-90 Degrees C	0-90 Degrees C	0-90 Degrees C	0-90 Degrees C
Approx Dims	700 x 570 x 800mm	1100 x 700 x 1130mm	1900 x 1250 x 1700mm	2200 x 1400 x 1800mm
Approx Dry Weight	65kgs	180kgs	900kgs	1200kgs
Max Fuel Consumption	7.5lts/Hour	15lts/Hour	30 Litres/hour	60 Litres/hour
Maxv Working Pressure	200-500 psi		4 bar	4 bar
Integral Pump	No	Yes	No	No
Water Inlet Connection	3/8" BSP Male	1" Geka	2" Male Camlock	2" Male Camlock
Water Outlet Connection	3/8" BSP Male	1" Geka	2" Male Hose Tail	2" Male Hose Tail
Power Supply (Volts/Amps)	1ph/13A/240V	1ph/13A/240V	1ph/13A/240V	3ph/16A/415V
Plug Type	3 Pin Blue Commando Plug	3 Pin Blue Commando Plug	3 Pin Blue Commando Plug	5 Pin Red Commando Plug
Fuel Tank Capacity	20 Litres	30 Litres	90 Litres	150 Litres
Handling	Wheeled	Wheeled	Forklift 2 way access	Forklift 2 way access

