

# RSM SPEEDY LINER (IES) SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

## SECTION ONE

### IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product Identifier

RSM Speedy Liner (integrated glide foil)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: construction industry

#### 1.3. Details of the supplier of the safety data sheet

Company Address: RSM Lining Supplies Global Ltd, Unit 2 Connection Business Park, Woodfield Way, Balby, Doncaster, DN4 8GE

Web: [www.rsm-web.com](http://www.rsm-web.com)

Telephone: +44 (0) 330 043 9604

Fax: N/A

Email: [info@rsm-web.com](mailto:info@rsm-web.com)

Email Address of the Competent Person: [sales@rsm-web.com](mailto:sales@rsm-web.com)

#### 1.4. Emergency telephone number

Emergency Telephone Number: +44 (0) 330 043 9604

Opening Hours: 8:30am - 5pm

## SECTION TWO

### HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Reproductive toxicity: Repr. 2

Specific target organ toxicity - single exposure: STOT SE 3

Specific target organ toxicity - repeated exposure: STOT RE 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Flammable liquid and vapour.



**RSM Lining Supplies**  
CHOICE AND TECHNOLOGY



**SPEEDYLINER**

RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: [sales@rsm-web.com](mailto:sales@rsm-web.com)  
WEBSITE: [www.rsm-web.com](http://www.rsm-web.com)

# RSM SPEEDY LINER (IES) SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

## SECTION TWO CONT.

### HAZARDS IDENTIFICATION

Causes skin irritation.  
Causes serious eye irritation.  
Suspected of damaging the unborn child.  
May cause respiratory irritation.  
Causes damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.  
Styrene data only applies to unhardened state.

#### 2.2. Label elements

**Regulation (EC) No. 1272/2008**

**Hazard components for labelling**

Styrene

**Signal word:** Danger

**Pictograms:**



#### Hazard statements

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P235 Keep cool.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P501 Dispose of contents/container to hazardous or special waste collection point.

#### Additional advice on labelling

The product is classified and labelled in accordance with the EC directives or respective national laws.



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES)

## SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

### SECTION TWO CONT.

#### HAZARDS IDENTIFICATION

#### 2.3. Other hazards

Styrene: Oxydising agents may form explosive peroxides.

Hardened material:

Product dust may be irritating to eyes, skin and respiratory system.

Fine dust dispersed in air may ignite.

### SECTION THREE

#### COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

##### Chemical characterization

Glass fibre reinforcement and mats impregnated with unsaturated polyester resin, dissolved in styrene and thickening agent.

##### Hazardous components

CAS No.	CHEMICAL NAME			QUANTITY
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
100-42-5	<b>Styrene</b>			20 - 30 %
	202-851-5	601-026-00-0	01-2119457861-32	
	Flam. Liq. 3, Repr. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 1, Asp. Tox. 1; H226 H361d H332 H315 H319 H335 H372 H304			
142-16-5	<b>Bis(2-ethylhexyl) maleate</b>			< 1,0 %
	205-524-5		01-2119524002-60	
	STOT RE 2, Aquatic Chronic 1; H373 H410			
162881-26-7	<b>Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide</b>			0.1 - < 1 %
	423-340-5		01-2119489401-38	
	Skin Sens. 1, Aquatic Chronic 4; H317 H413			

Full text of H and EUH statements: see section 16.

##### Further Information

Styrene data only applies to unhardened state.



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES)

## SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

### SECTION FOUR

#### FIRST AID MEASURES

##### 4.1. Description of first aid measures

###### General information

Protection is needed for the First Aider. Show this safety data sheet to the doctor in attendance.

###### After inhalation

Move out of dangerous area. Fresh air supply. Oxygen or artificial respiration, if needed. Lay the affected person down, and keep her or him warm and calm. Call a physician immediately.

###### After contact with skin

Wash contaminated skin areas thoroughly with soap and water. Remove soiled clothing. If symptoms persist, call a physician.

###### After contact with eyes

Rinse with plenty of water immediately, also under the eyelids, for at least 15 minutes. Consult an ophthalmologist immediately.

###### After ingestion

Do not induce vomiting. If a person vomits when lying on their back, place them in the recovery position. Keep the respiratory tract open, prevent aspiration. Never give anything by mouth to an unconscious person. Rinse mouth. Clean mouth with water and drink plenty of water afterwards. Call a physician immediately.

##### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation of vapours is irritating to the respiratory system and may cause sore throat pain and coughing.

Skin irritation, erythema, Irritation of mucous membranes, lachrymation.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

May cause headache and dizziness.

##### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment (decontamination and vital functions).

### SECTION FIVE

#### FIREFIGHTING MEASURES

##### 5.1. Extinguishing media

###### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, dry chemical.

Water mist may be used to cool closed containers.

###### Unsuitable extinguishing media

High volume water jet.

##### 5.2. Special hazards arising from the substance or mixture

Depending on the conditions of the fire, the following combustion products could be formed/ given off: carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO). Vapours may form explosive mixtures with air.

##### 5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus and protective suit. In the case of respirable dust and/or fumes, use self-contained breathing apparatus and dust impervious protective suit.

###### Additional information

Contaminated extinguishing water and soil must be disposed of in accordance with official regulations.



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES)

## SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

### SECTION SIX

#### ACCIDENTAL RELEASE MEASURES

##### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid bringing product in contact with the skin. Keep away from sources of ignition - No smoking. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe in vapours. When handling the product, follow hygiene and safety precautions. (See section 7 and 8)

##### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Avoid subsoil penetration. Contact the responsible authority immediately if the product ends up in the soil, a body of water, or the sewer system.

##### 6.3. Methods and material for containment and cleaning up

Seal discharge point, if possible without danger. Use mechanical handling equipment. Spilled or leaking material is to be soaked up with non-flammable absorbent materials (sand, soil, diatomaceous earth) and put in containers. Use only explosion-proof equipment. Disposal in accordance with the official regulations.

##### 6.4. Reference to other sections

Refer to safety instructions (see sections 7 and 8).

Suitable protective equipment: See section 8.

Dispose of as described in section 13.

### SECTION SEVEN

#### HANDLING & STORAGE

##### 7.1. Precautions for safe handling

###### Advice on safe handling

Provide adequate ventilation and/or exhaust ventilation. (Styrene: Vapours are heavier than air and may spread along floors.) Protect from light. The product should only be used in areas from which all uncovered lights and other sources of ignition have been excluded. When using, do not eat, drink, or smoke. Avoid dust formation. Do not breathe vapours/dust. Wear personal protective equipment. (See section 8.)

###### Advice on protection against fire and explosion

Vapours may form explosive mixtures with air. Take precautionary measures against static discharges. Use only explosion-proof equipment.

###### Further information on handling

When using, do not eat, drink, or smoke. When handling the product, follow hygiene and safety precautions.

##### 7.2. Conditions for safe storage, including any incompatibilities

###### Requirements for storage rooms and vessels

Store in compliance with the local regulations. Keep at temperature not exceeding 25 °C. Protect from direct sunlight. Keep tightly closed in a dry, cool and well-ventilated place. Avoid contamination with incompatible materials. Keep away from sources of ignition - No smoking. Should not be released into the environment. Store in a cool and shaded area.



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES)

## SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

### SECTION SEVEN CONT.

#### HANDLING & STORAGE

##### Advice on storage compatibility

Store separately from: Oxidising agents.

Keep away from food, drink and animal food stuffs.

##### 7.3. Specific end use(s)

No data available.

### SECTION EIGHT

#### EXPOSURE CONTROLS/PERSONAL PROTECTION

##### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
100-42-5	Styrene	100	430		TWA (8 hours)	WEL
		250	1080		STEL (15 minutes)	WEL

##### DNEL/DMEL values

CAS No.	SUBSTANCE		
DNEL type	Exposure route	Effect	Value
162881-26-7	Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide		
Worker DNEL, long-term	inhalation	systemic	21 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	21 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	3,3 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	3,3 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	5,2 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	1,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	1,5 mg/kg bw/day

##### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation and/or exhaust ventilation. Follow the maximum workplace concentration values. Local exhaust.

Use only explosion-proof equipment.

##### Protective and hygiene measures

When using, do not eat, drink, or smoke.

Wash hands before breaks and at the end of the workday .

Eye wash fountains and safety showers must be easily accessible.

##### Eye/face protection

Safety glasses with side-shields.



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES) SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

## SECTION EIGHT CONT.

### EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
100-42-5	Styrene	100	430		TWA (8 hours)	WEL
		250	1080		STEL (15 minutes)	WEL

#### DNEL/DMEL values

CAS No.	SUBSTANCE		
DNEL type	Exposure route	Effect	Value
162881-26-7	Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide		
Worker DNEL, long-term	inhalation	systemic	21 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	21 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	3,3 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	3,3 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	5,2 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	1,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	1,5 mg/kg bw/day

#### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation and/or exhaust ventilation. Follow the maximum workplace concentration values. Local exhaust.

Use only explosion-proof equipment.

##### Protective and hygiene measures

When using, do not eat, drink, or smoke.

Wash hands before breaks and at the end of the workday.

Eye wash fountains and safety showers must be easily accessible.

##### Eye/face protection

Safety glasses with side-shields.

##### Hand protection

Solvent-resistant gloves The manufacturer recommends the following glove materials :

- fluorinated rubber (viton). Penetration time of the glove material: >8 h, layer thickness: 0,70 mm.

- chloroprene rubber / nitrile rubber. Penetration time of the glove material: <1 h, layer thickness: 0,2 mm. Safety gloves should be selected for the actual conditions of use and in accordance with the instructions for use provided by the manufacturer.

Protective gloves should be replaced immediately if damaged or in case of signs of wear.

##### Skin protection

Dust impervious protective suit.



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES)

## SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

### SECTION EIGHT CONT.

#### EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Respiratory protection

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Do not breathe in vapours. Hardened material: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.

Respirator with combination filter for vapour/particulate.

### SECTION NINE

#### PHYSICAL AND CHEMICAL PROPERTIES

##### 9.1. Information on basic physical and chemical properties

Physical state: paste \*

Colour: green \*

Odour: characteristic \*

pH-Value: n.a

##### Changes in the physical state

Melting point: n.a.

Initial boiling point and boiling range: 146 (Styrene) °C

Flash point: 33 (Styrene) °C ISO 1523

Lower explosion limits: No data available.

Upper explosion limits: No data available.

Vapour pressure: No data available.

Density (at 23 °C): 1,5 g/cm<sup>3</sup>

Water solubility: insoluble

##### Solubility in other solvents

No data available.

Partition coefficient: log Pow: 2,96 (Styrene)

Viscosity / dynamic: > 100000 mPa·s

Vapour density: No data available.

Evaporation rate: No data available.

##### 9.2. Other information

\* = uncured material



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com



# RSM SPEEDY LINER (IES)

## SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

### SECTION TEN

#### STABILITY & REACTIVITY

##### 10.1. Reactivity

No data available.

##### 10.2. Chemical stability

Stable at normal conditions.

##### 10.3. Possibility of hazardous reactions

No dangerous reactions occur under normal storage conditions and in normal use.

##### 10.4. Conditions to avoid

Protect from direct sunlight. Keep away from sources of ignition - No smoking.

##### 10.5. Incompatible materials

oxidising agents (Styrene : Oxydising agents may form explosive peroxides.)

Exothermic reaction with strong acids.

Avoid exothermic reactions with peroxides.

##### 10.6. Hazardous decomposition products

No data available.

##### Further information

Becomes warm when polymerized.

### SECTION ELEVEN

#### TOXICOLOGICAL INFORMATION

##### 11.1. Information on toxicological effects

##### Toxicocinetics, metabolism and distribution

No data is available on the product itself.

##### Acute toxicity

CAS No.	CHEMICAL NAME				
	Exposure route	Dose	Species	Source	Method
100-42-5	<b>Styrene</b>				
	oral	LD50 2650 mg/kg	rat	GESTIS	
	inhalation (4 h) vapour	LC50 12 mg/l	rat	GESTIS	
	inhalation aerosol	ATE 1,5 mg/l			
162881-26-7	<b>Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide</b>				
	oral	LD50 > 2000 mg/kg	rat	Supplier	
	dermal	LD50 > 2000 mg/kg	rat	Supplier	



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES)

## SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

### SECTION ELEVEN

#### TOXICOLOGICAL INFORMATION

##### **Irritation and corrosivity**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Inhalation of vapours is irritating to the respiratory system and may cause sore throat pain and coughing.

Skin contact: Irritating to skin. Main symptoms: redness.

Eye contact: Severe eye irritation. Material sprayed or splashed into the eyes can cause symptoms or injuries such as redness, tearing and corneal damage.

Effects due to ingestion may include: Mucous membrane irritations in the mouth, throat, oesophagus and gastrointestinal tract.

##### **Carcinogenic/mutagenic/toxic effects for reproduction**

Styrene: IARC: 2B

##### **STOT-single exposure**

Irritation of the respiratory tract, eyes and/or skin possible.

##### **STOT-repeated exposure**

Central nervous system disorders

##### **Specific effects in experiment on an animal**

Irritation of mucous membranes,

Irritation to respiratory organs

Central nervous system disorders (daze, headache and lack of concentration).

### SECTION TWELVE

#### ECOLOGICAL INFORMATION

##### **12.1. Toxicity**

No data is available on the product itself.

Styrene:

EC50/Algae/72h: 4,9 mg/l

LC50/Fish (Fathead minnow)/96h: 4,02 mg/l

NOEC/Daphnia magna/21 d: 1,01 mg/l

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide :

Toxicity to algae:

IC50/Algae/72h: >260 µg/l , (Desmodesmus subspicatus)

Daphnia toxicity:

LC50/Daphnia magna/48d: >1175 µg/l

Acute toxicity to fish:

LC50/Fish/96h: > 90 µg/l, Brachydanio rerio

-----

NOEC = No-Observed-Effect-Concentration



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES)

## SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

### SECTION TWELVE CONT.

#### ECOLOGICAL INFORMATION

##### 12.2. Persistence and degradability

Styrene: Readily biodegradable, according to appropriate OECD test.

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide : Not easily biodegradable.

##### 12.3. Bioaccumulative potential

No major bioaccumulation.

##### Partition coefficient n-octanol/water

CAS No	CHEMICAL NAME	Log Pow
100-42-5	Styrene	3,05
162881-26-7	Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	5,8

##### BCF

CAS No	Chemical name	BCF	Species	Source
162881-26-7	Phenylbis(2,4,6-trimethylbenzoyl)-phosphineoxide	< 5	Carp (Cyprinus carpio)	

##### 12.4. Mobility in soil

No data is available on the product itself.

##### 12.5. Results of PBT and vPvB assessment

None known.

##### 12.6. Other adverse effects

None known.

##### Further information

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Avoid subsoil penetration.

### SECTION THIRTEEN

#### DISPOSAL CONSIDERATIONS

##### 13.1. Waste treatment methods

###### Advice on disposal

Unhardened (pasty) product waste, contaminated packaging as well as product residues on protective clothing can harden through daylight exposure. If the UV protection foil exists, it should be removed.

Hardened material : Dispose of exposed material as cured plastic waste. (EWC 070213)

uncured material : Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Avoid subsoil penetration.

Must be sent for special treatment in accordance with local authority regulations. Offer surplus and non-recyclable solutions to a licensed disposal company.



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES) SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

## SECTION THIRTEEN CONT.

### DISPOSAL CONSIDERATIONS

#### **Waste disposal number of waste from residues/unused products**

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

#### **Waste disposal number of used product**

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

#### **Waste disposal number of contaminated packaging**

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

#### **Contaminated packaging**

Dispose of non-cleansing packaging in the same way as the product.

## SECTION FOURTEEN

### TRANSPORT INFORMATION

#### **Other applicable information**

Not classified as dangerous regarding transport regulations.

## SECTION FIFTEEN

### REGULATORY INFORMATION

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU regulatory information

#### **Additional information**

No Substances of Very High Concern (SVHC) according REACH Article 57.

#### **National regulatory information**

Water contaminating class (D): 2 - clearly water contaminating



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com

# RSM SPEEDY LINER (IES) SAFETY DATA SHEET

VERSION: 1.01

VERSION DATE: 06/12/2018

## SECTION SIXTEEN

### OTHER INFORMATION

#### Abbreviations and acronyms

n.a. = not applicable

n.d. = not determined

SVHC = substance of very high concern

#### Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 1; H372	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

#### Further Information

The information is based on present levels of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The product is to be used exclusively for the applications named in the technical data sheet or in the processing instructions. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



RSM Lining Supplies Global Ltd  
Unit 2, Doncaster, UK, DN4 8GE  
PHONE: +44 (0)330 043 9604  
EMAIL: sales@rsm-web.com  
WEBSITE: www.rsm-web.com